

Thermal									
- Chassis cooling fan	92 mm	120 mm	80 mm	92 mm	120 mm	3 x Dual 40 mm	3 x 80 mm	3 x 80 mm	3 x 80 mm
- Fan failure alert	√	√	√	√	√	√	√	√	√
- High temperature alert with auto-shutdown option	√	√	√	√	√	√	√	√	√
Noise									
- Typical at 1 meter distance	31.5 dBA	25 dBA	25 dBA	31.5	25 dBA	50 dBA+			
Operating Environment									
- Temperature	0 - 40° C	0 - 40° C	0 - 40° C	0 - 40° C	0 - 40° C	0 - 40° C	0 - 40° C	0 - 40° C	0 - 40° C
- Humidity (non-condensing)	20% - 80%	20% - 80%	20% - 80%	20% - 80%	20% - 80%	20% - 80%	20% - 80%	20% - 80%	20% - 80%
- FCC, CE, C-tick, KCC, VCCI, RoHS compliance	√	√	√	√	√	√	√	√	√
Warranty									
- Coverage	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years

* Optional dual SFP+ or CX-4 10G interfaces on the 4200

** 500GB drives used in NVX are non-enterprise drives.